



- Tile Adhesive
- Tile Grout
- Tiles Epoxy Grout
- Wall Putty





OUR VISION AND MISSION

INTRODUCTION

STRONG BOND is a leading provider of construction chemicals, specializing in high-quality adhesives, grouts, and waterproofing solutions. With a commitment to innovation and excellence, we deliver products that enhance the durability and aesthetics of construction projects.

MISSION

To provide superior construction solutions that build stronger, more sustainable structures while fostering long-term customer relationships

VISION

To be the most trusted and innovative construction chemicals company globally

INDEX

TILE ADHESIVE-GOLD	03
TILE ADHESIVE-GOLD PLUS	04
TILE ADHESIVE-PLATINUM	05
TILE ADHESIVE-DIAMOND	06
BLOCK ADHESIVE	07
READY MIX PLASTER	08
WALL PUTTY	09
TILE GROUT	10
EPOXY GROUT	11
SBR	13
IWP	14
TILES CLEANER	15
PRIMER	16
AAC BLOCK	17
TILE ACCESSORIES	18



APPLICATION

Polymer modified grey cement based tile adhesive for fixing ceramic tiles, natural stone & vitrified tiles in interior area

KEY FEATURES & BENEFIT

- Single component just add water
- Polymer modified
- Better Work ability
- Cost Efficient

COVERAGE

Coverage is based on smoothness of substrate and thickness of mortar used. For a 3mm bed thickness the coverage will be 35-40 Sq.Feet per 20 kg. Bag.

SHELF LIFE & STORAGE

Best Before 12 Month from the date of manufacturing in unopened condition. Store in a cool & dry place

PACKING

20 kg.



APPLICATION

Polymer modified tile adhesive for fixing tiles internal and externally. It gives excellent bond on concrete and plaster like surface.

KEY FEATURES & BENEFIT

- Single component just add water
- Easy to use & better work ability
- Water Resistant
- Excellent Adhesion & strength
- Ensure permanent fixing

COVERAGE


Coverage is based on smoothness of substrate and thickness of mortar used. For a 3mm bed thickness the coverage will be 35-40 Sq.Feet per 20 kg. Bag.

SHELF LIFE & STORAGE

Best Before 12 Month from the date of manufacturing in unopened condition. Store in a cool & dry place

PACKING

20 kg.



APPLICATION

Strong Bond Platinum is a cement based adhesive for wall and floor tiles. Suitable for fixing tiles and natural stones in interior and exterior situations which includes swimming pools. This is ideal for fixing tile on tile.

KEY FEATURES & BENEFIT

- Single component just add water
- Polymer modified
- High bond strength
- Economical & easy to use

COVERAGE

Coverage is based on smoothness of substrate and thickness of mortar used. For a 3mm bed thickness the coverage will be 35-40 Sq.Feet per 20 kg. Bag.

SHELF LIFE & STORAGE

Best Before 12 Month from the date of manufacturing in unopened condition. Store in a cool & dry place

PACKING

20 kg.



APPLICATION

High Polymer modified tile adhesive for fixing tiles internal and externally. It gives excellent bond on concrete and plaster (Application on Size: 800x1600, 1200x1200, 1200x2400 all Slab tile Marble & Granites wall & Floor both)

KEY FEATURES & BENEFIT

- Single component just add water
- Highly polymer modified
- Easy to use & better work ability
- Water and sock resistant
- Bonds to various substrates
- Excellent Adhesion & flexural strength
- Ensure permanent installation

COVERAGE

Coverage is based on smoothness of substrate and thickness of mortar used. For a 3mm bed thickness the coverage will be 35-40 Sq.Feet per 20 kg. Bag.

SHELF LIFE & STORAGE

Best Before 12 Month from the date of manufacturing in unopened condition. Store in a cool & dry place

PACKING

20 kg.



DESCRIPTION

Strong Bond Block Adhesive is a factory prepared blend of carefully selected raw materials, Portland cement, graded aggregates and polymers. Designed for use with water to produce high strength thixotropic mortar ideal for laying aerated light weight concrete, fly ash bricks, cement hollow blocks, cellular concrete blocks or smoothing over the block work surface in layers of up to 12mm thickness that meet and exceed the requirements of National and international Standards.

KEY FEATURES & BENEFIT

- Strong Bonding
- No curing required after block work is done
- Improved adhesion between two block
- Fast & economical

COVERAGE

Approximately 100-130 sq.ft. per 40kg bag. Coverage is based on smoothness and evenness of the substrate, size of blocks used and the thickness of mortar used. A general guideline for coverage of mortar is given when used with 25% water added to powder.

PACKING

40 kg.



DESCRIPTION

Strong Bond Ready Mix Plaster, is a polymer modified premixed cement based plaster. it can be used on interior and exterior wall surface. It is cost-effective, easy to use, stronger and bonds better to its substrate. Provides an even surface on which tiling can be done faster and more efficiently.

KEY FEATURES & BENEFIT

- High Strength
- Cracks free wall
- Faster Application
- Excellent Coverage
- Economical

COVERAGE

A 40kg. bag of Strong Bond Ready Mix Plaster covers 15-20 sq. ft. at coverage of 10 -12 mm thickness. Coverage depends upon quality and nature of substrate being used

SHELF LIFE & STORAGE

Best Before 12 Month from the date of manufacturing in unopened condition. Store in a cool & dry place

PACKING

40 kg.



DESCRIPTION

Strong Bond Wall Putty is a cement based premium quality putty which comes in powder form. With excellent filling and surfacing characteristics, strong bonding abilities and minimal dust, the putty is best suited to provide smooth aesthetic finish and extend the life of top coat paints.

KEY FEATURES & BENEFIT

- Low Dusting
- Quick Drying
- Easy Application
- Water Resistant
- Smooth Finish

SHELF LIFE & STORAGE

Best Before 12 Month from the date of manufacturing in unopened condition. Store in a cool & dry place

PACKING

40 kg.



DESCRIPTION	High quality fine, polymer-modified, water-resistant, cement-based powder grout designed for grouting glazed wall tiles, mosaics, vitrified & fully vitrified tiles, floor tiles, industrial floor tiles etc.,
FEATURES	Polymer modified grout. Good compressive strength. Available in range of colours Depends on substrate
SHELF LIFE & STORAGE	Best Before 12 Month from the date of manufacturing in unopened condition. Store in a cool & dry place
PACKING	1 kg.

AVAILABLE COLOUR

				
WHITE	IVORY	LIGHT GREY	SKY BLUE	PINK
				
WOODEN	CHOCOLATE	BLACK	ALPHA BLUE	C.BROWN
				
AQUA GREEN	TERRA COTTA	JESALMER	DARK GREY	DARK BROWN



DESCRIPTION Epoxy Grout is a three-part system, comprising of PART A, PART B and PART C for ease of application. The ability to fill tile / stone joints. The grout is best mixed to a smooth, creamy consistent paste. Epoxy resin based grout has a high degree of resistance to chemicals, abrasion and higher impact resistance. The cured grout creates a tough, impermeable layer-resistant to food drops, bacteria, and dirt is easily maintained in a clean condition.

FEATURES Stain less and easy to clean, easy to mix and apply. Provides excellent chemical resistant property. Provides hygienic, hard wearing & impervious properties. Non-cracking or powdering. Non-Toxic & restricts entry of bacteria / dirt.

PACKING 1 kg & 5 kg

30+ Colours Available






PURE WHITE



BRIGHT WHITE



BLACK



MOCHA



PERCHMENT



PLATINUM



SILK



SPECTRA PINK



IVORY



SAGA



MARBLE BEIGE



CANYON RED



CADMIUM RED



QUARRY RED



SILVER SHADOW



BUFF



SABLE



RAVEN



JAISALMER



BURGANDY



SMOKE GREY



DUSTY ROSE



NATURAL GREY



DARK GREY



HEMP



ORANGE



INCA GOLD



VIOLET



BLUE



SKY BLUE



NAVY BLUE



OLIVE GREEN



LEMON YELLOW



IVY

**PRODUCT
DETAILS**

STRONG BOND SBR is a highly potent and versatile SBR based liquid for high performance applications in waterproofing and repairs.

**TECHNICAL
INFORMATION**

- Type - Styrene Butadiene Polymer Liquid
- Color - White
- Specific Gravity - 1.02 + 0.02
- Storage Condition - Free from frost
- Solid Content - 44 + 1 %
- For best result - Use before 1 year if unopened Consumption - 1ltr of Strong Bond SBR will cover 70-80sq. ft. area in 2 coats for a proportion mix 1:4:7 (Strong Bond SBR : Water : Cement)

PACKING

1Ltr. & 5 Ltr.



DESCRIPTION


STRONG BOND IWP is specially formulated integral liquid waterproofing compound of surface active plasticising agents, polymers & additives. It is used as an additive for cement concrete, mortar & plasters. It makes concrete cohesive and prevents segregation.

FEATURES

- Corrosion resistant - Make concrete more cohesive, hence protects steel better against corrosion
- Compatibility - Being a liquid, easily dispersible & compatible with concrete/mortar mixes.
- Permeability - It reduces the permeability of water into concrete.
- Strength - The setting time and compressive strength of the concrete remains within the specification limits.
- Shrinkage - Reduces shrinkage crack development in plaster & concrete.
- Workability - Improves workability of freshly mixed cement concrete.
- Durability - Increases durability by improving waterproofing of concrete.

PACKING

1Ltr. & 5 Ltr.



DESCRIPTION STRONG BOND Tiles cleaner is a fast acting acid based cleaner for regular cleaning of dirt stains on tile surface. Tile Cleaner is designed for daily maintenance of tiles. It is ideal for interior and exterior use.

APPLICATION Unglazed Ceramic Tiles, Glazed Ceramic Tiles, Vitrified Tiles, Porcelain tiles & Glass

COVERAGE Varies as per application

PACKING 1 Ltr. & 5 Ltr.



DESCRIPTION STRONG BOND PRIMER is a white cement based water thinnable liquid primer, that provides more adhesion and higher coverage than pure water based acrylic wall primers available in the market. It prevents the peeling of your wall topcoat and protects your walls for years to come. This product also provides the best possible opacity and whiteness needed to bring out the true colour tones of your wall paint.

COVERAGE INTERIOR - 200-230sq.ft/Ltr.
EXTERIOR - 110-140sq.ft/Ltr.

PACKING 1 Ltr. & 5 Ltr.





APPLICATION	High Strength AAC Block Available in all sizes
KEY FEATURES & BENEFIT	<ul style="list-style-type: none">• Light Weight• Easy to Carry• Faster Construction Time• Excellent Thermal & Sound Insulation• Fire Resistance
COVERAGE	Depends on Block Size
SIZES	4", 6", 8", 9", 12"



TILE SPACERS



TILE LEVELLERS



TROWELS




Trowel Size
6mm, 8mm,
10mm Available



TILE LIFTER



Tiles Adhesive Direction of Use



REMOVE ANY OIL, DUST AND GREASE.
तेल, ग्रीस, और धूल मिटी को हटाये



POUR WATER INTO THE BUCKET.
खाली बाल्टी में पानी डालें



ADD THE POWDER AND MIX.
पाउडर को उसमें डालें और मिक्स करें



MIX THOROUGHLY PREFERABLY WITH MECHANICAL STIRRER OR MANUALLY.
समतुलित पेस्ट बनाने के लिये सही मिश्रण करें



APPLY THE ADHESIVE ON THE SURFACE WITH THE SMOOTH PART OF THE TROWEL.
सतह पे एडेसिव फैलाने के लिये, ट्रोवेल के सपाट हिस्से का इस्तेमाल करें



SPREAD THE ADHESIVE USING THE TOOTHED PART OF THE TROWEL
एडेसिव को उपयुक्त मोड़ा देने के लिये ट्रोवेल के दातो वाला हिस्सा इस्तेमाल करें



AS PER REQUIREMENT DO BACK BUTTERING ON TILE.
बड़ी साइज की टाइल्स के लिये एडेसिव को टाइल्स के पिछे जरूर लगाये



START PLACING THE TILES ON THE SURFACE. TAP THE TILE PROPERLY TO ENSURE COMPLETE COVERAGE ON THE BACK SIDE OF TILES.
टाइल लगाई जा रही सतह पर टाइल्स रखना शुरू करें, टाइल्स को हल्के से ढीके ताकि टाइल्स के पिछले हिस्से पर पूर्ण कवरेज मिल सके.



REMOVE EXCESS ADHESIVE FROM THE TILE SURFACE.
जरूरत से ज्यादा एडेसिव टाइल की सतह पर है तो निकाल लें







GROUT 24 H AFTER FIXING.
फिक्सिंग के %, घंटे बाद साथे भरे

Tile Adhesive VS Sand-Cement Mortar

Tile Adhesives	Sand-Cement Mix
Fast and efficient, easy to use, only mix with water.	Time consuming.
No prior soaking of tiles is required.	Variety Of Tiles must be soaked.
Better bonding strength.	Moisture can accumulate beneath the floor tile and wall tiles, causing hollow spaces and debonding.
Can be grouted within 24 hours without waiting for the moisture to evaporate.	Grouting cannot be done within 24 hours.
The application can be done on existing tiles and many special substrates like polished cement, dry wall system, etc.	Not applicable to lay low absorbent tiles like 60 x 60 cm granite or any larger tile sizes.
	Not applicable to lay tiles on existing tiles, and on polished cement.
	Not applicable to lay glass mosaics.
Tile adhesive typically has a smooth slurry that helps create a thinner layer when applying it for natural stone, ceramic tiles, and other wall tiles installation.	Cement-Sand slurry are usually thicker in consistency, making it difficult to spread an even layer onto the surface.

TIRUPATI MINERALS

-  Plot No.2, Latur Road, Dhanegaon
Nanded 431603.
-  Web : www.strongbondchem.com
-  E-mail : contact@strongbondchem.com
-  Customer Care : +91 70793 17655



Follow us on :    